

IN20042WH INSTALLATION INSTRUCTIONS

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102
Phone: (866) 845-5451. Fax: (866) 816-6165
www.acclaim-lighting.com

ACCLAIM
LIGHTING
INTERIOR • OUTDOOR

Please read carefully and save these instructions as you may need them a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Thread 3" Rod to the Coupling of the fixture body, and then connect 1*3" Rod, 1*6" Rod, 3*12" Rod, and Join together with Couplings. Repeat for second rod assembly.
2. Place the Canopy onto the Joint, then attach Gear washer and Spring washer to the Joint, then fasten them with Butterfly Nut.
3. Drill two holes into the ceiling (measure distance of holes according to the holes on the canopy) then push the Anchors into the holes.
4. Thread the two Support Screws to the Cross Bar with Hex Nut.
5. Attach the cross bar to the outlet box, then use the two mounting screws and wood screws to tighten the cross bar.
6. Make wire connections:
 - The ridged wire (unmarked) from the fixture to white wire from power source.
 - The smooth wire (marked) from the fixture to black wire from power source.
 - Loop the ground wire to cross bar with a green screw.
7. Place the Canopy over the Outlet Box through the two Support Screws and thread with two Ball Nuts.
8. Install bulbs: (Bulbs not included). (Don't exceed the maximum capacity recommended on the sockets).

INSTALLATION IS NOW COMPLETED.

